

e a o

Your Expert Partner for Human Machine Interfaces

# Single- LED

Distribution by  
Mouser



10-2112.1064



<https://mouser.eao.com/component/10-2112.1064...>

Your product:



10-2112.1064  
Single-LED

#### OPERATING-/INDICATION PART

**Illumination colour:** Yellow

#### ELECTRICAL CHARACTERISTICS

**Operating voltage:** 24 V AC/DC +10%

**Operation current:** 7 - 14 mA ±15 %

**Lumi. Intensity:** 280 mcd

#### MECHANICAL CHARACTERISTICS

**Weight:** 0.001 kg

#### CERTIFICATE

**REACH:** REACH compliant


**RoHS:** RoHS compliant

#### OTHER

**Short Description:** Single-LED, T5.6, Yellow, 24 V AC/DC +10%

**Hints:** For LED element fitting information see Application guidelines, LED polarity  
Due to high surface temperatures, the series resistor must not be soldered directly  
to the terminals of the equipment (use a terminal plate)  
When using AC/DC types with AC operation, slight flickering can occur  
The luminous intensity stated is for when used with DC  
Electrical and optical data are measured at 25 °C  
The specified versions are built with a protection diode (half wave rectifier) in  
series and the LED  
Luminosity and wave length variations caused by LED manufacturing processes  
may cause slight differences regarding the illumination. The customer has to  
decide what resistor shall be used to the LED  
Where supply voltages are over 48 V, a voltage-reduction element (external  
protective series resistor) must be used.

**Wiring diagrams:**



**Dimension drawings:**

