

Actuator

18-

188.035

Distribution by Mouser









18-188.035 Actuator

FRONT	
Front dimension:	19 mm x 19 mm
Front form:	Square
Front bezel colour:	Black
Front bezel material:	Plastic
MOUNTING	
Design:	Flush
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lens illumination:	Illuminated
ELECTRICAL CHARACTERISTICS	
Switching voltage and switching current:	100 mA at 42 VAC/VDC
Contacts:	1 NC
Switching rating:	42 V @ 0,1 A
Electrical lifetime:	≥500 000 cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1
Electric strength:	500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

MECHANICAL CHARATERISTIC

Terminal: Soldering terminal

Contact material: Gold

Switching action: Momentary

Switching system: Snap-action switching element

Switching system: The snap-action switching system was designed for switching low powers in

electronic circuits. Single-break snap-action contact.

Mechanical lifetime: 2 Mil. cycles of operation

Operating force: 1.4 N

Operating Travel: ca. 2.2 mm \pm 0.2 mm

Tightening torque: Fixing nut max. 0.2 Nm

Wire cross section: Max. wire cross-section 2 wires with 0.5 mm

Max. wire cross-section of stranded cable 1 x 0.75 mm²

Wire cross-section of terminal 1,6 x 0,4 mm²

Weight: 0.002 kg

AMBIENT CONDITION

IP front protection: IP40, according to IEC 60529

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... \, + 65 \, ^{\circ}\text{C}$

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$

Shock resistance: 50 g for 11 ms, as per DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal)

Vibration resistance: 10 g at 10 Hz...2000 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN

60512-4-4

CERTIFICATE

Conformities: 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD) for version 230 VAC

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, 19 mm x 19 mm, Illuminated, Square, Black, Plastic, 1 NC, Momentary,

Soldering terminal, IP40, according to IEC 60529


Internal size: 13,8 mm x 13,8 mm

Housing colour: Black


Housing material: Plastic

Product attributes: +/- terminals are not connected

Wiring diagrams:



Component layouts:




A = Terminals (rear side)

B = Illuminated pushbutton
C = x = Contact No.

D = 2 = Normally open E = 4 = Normally close

Mounting cut-outs:



Dimension drawings:

