

# Actuator

18-

247.035

Distribution by Mouser









## 18-247.035 Actuator

Е	D	0	N	٦
г	п	v	14	

Front dimension: 14 mm x 9 mm

Front form: Rectangular

Front bezel colour: Black

Front bezel material: Plastic

#### **MOUNTING**

Design: Raised

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lens illumination: Illuminated

## **ELECTRICAL CHARACTERISTICS**

Switching voltage and switching

current:

100 mA at 42 VAC/VDC

Contacts: 1 NO

Switching rating: 42 V @ 0,1 A

**Electrical lifetime:** ≥500 000 cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1

**Electric strength:** 500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

#### **MECHANICAL CHARATERISTIC**

**Terminal:** Soldering terminal

Contact material: Gold

Switching action: Maintained

**Switching system:** Snap-action switching element

**Switching system:** The snap-action switching system was designed for switching low powers in

electronic circuits. Single-break snap-action contact.

**Mechanical lifetime:** 1 Mil. cycles of operation

Operating force: 1.4 N

**Operating Travel:** ca. 2.2 mm  $\pm$  0.2 mm

**Tightening torque:** Fixing nut max. 0.2 Nm

Wire cross section: Max. wire cross-section 2 wires with 0.5 mm

Max. wire cross-section of stranded cable 1 x 0.75 mm<sup>2</sup>

Wire cross-section of terminal 1,6 x 0,4 mm<sup>2</sup>

**Weight:** 0.002 kg

#### **AMBIENT CONDITION**

**IP front protection:** IP40, according to IEC 60529

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... \, + 65 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$ 

**Shock resistance:** 50 g for 11 ms, as per DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal)

Vibration resistance: 10 g at 10 Hz...2000 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN

60512-4-4

#### **CERTIFICATE**

**Conformities:** 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD) for version 230 VAC

**REACH:** REACH compliant

**RoHS:** RoHS compliant

#### **OTHER**

Short Description: Actuator, 14 mm x 9 mm, Illuminated, Rectangular, Black, Plastic, 1 NO,

Maintained, Soldering terminal, IP40, according to IEC 60529


**Internal size:** 12,5 mm x 7,5 mm

Housing colour: Black


Housing material: Plastic

**Product attributes:** +/- terminals are not connected

Wiring diagrams:



## **Component layouts:**



A = Terminals (rear side)


B = Illuminated pushbutton

C = x = Contact No.

D = 2 = Normally open

E = 4 = Normally close

## Mounting cut-outs:



## Dimension drawings:

