

Actuator

45-2131.21K0.000 Distribution by Mouser









45-2131.21K0.000 Actuator

	_	_		-
ь.	к	()	N	

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Colourless

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: transparent

Lens type: Level with front bezel

MECHANICAL CHARACTERISTICS

Switching action: Momentary


Switching system: Slow-make switching element

Mechanical lifetime: 500 000 cycles of operation

Weight:	0.038 kg	
AMBIENT CONDITION		
IP front protection:	IP66, IP67, IP69K	
Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, Flush, Non illuminated, Colourless, Plastic, transparent, Round, Silver, Metal, Momentary, IP66, IP67, IP69K	
Housing colour:	Silver	
Housing material:	Metal	
Wiring diagrams:		
	_	
Mounting cut-outs:		

Max. 3 600/h

Operating frequency:



Dimension drawings:

