

Your Expert Partner for Human Machine Interfaces

Actuator

61-4610.0

Distribution by Mouser







https://mouser.eao.com/p/61-4610.0

Your product:



61-4610.0 Actuator

NA.	\mathbf{n}		IT	'IN	0
IVI	U	υı	N I.	IIN	u.

Mounting type:

Panel mounting

OPERATING-/INDICATION PART

Lever material:	plastic
Lever shape:	short

MECHANICAL CHARACTERISTICS

Switching action:	Maintained - Rest - Maintained	
Switching positions:	3 positions	
Switching angle:	90° left / 90° right	
Mechanical lifetime:	According to DIN/IEC 60512-5-6 and EN/IEC 60947-5-1, 100 000 cycles of operation	
Operating force:	0.0250.1 Nm snap-action switching element, 0.4 0.16 Nm slow-make switching element	
Operating Travel:	ca. 2 x 90°	
Tightening torque:	Max. 0.5 Nm	
Weight:	0.006 kg	

AMBIENT CONDITION

IP Protection:	IP40 rear side, according to EN IEC 60529, IP67 front side, according to EN IEC 60529
Operating temperature:	– 25 °C + 55 °C
Storage temperature:	– 40 °C + 85 °C

CERTIFICATE

REACH:	REACH compliant
RoHS:	RoHS compliant

OTHER

Short Description:

Actuator, optional illuminative, short, Maintained - Rest - Maintained


Housing material:

Product attributes:

Switching positions:

Plastic, according to UL 94 V0, self-extinguishing


Illuminative



Wiring diagrams:




Mounting cut-outs:




A = Solder/Plug-in terminal 2.8 mm x 0.5 mm


C = Screw terminal



A = Solder/Plug-in terminal 2.8 mm x 0.5 mm C = Screw terminal




 $\begin{array}{l} \mathsf{A} = \text{Solder/Plug-in terminal 2.8 mm x 0.5} \\ \mathsf{mm} \\ \mathsf{C} = \text{Screw terminal} \end{array}$




A = Solder/Plug-in terminal 2.8 mm x 0.5 mm

C = Screw terminal


Dimension drawings:




- A = Plug-in terminal 2.8 mm x 0.5 mm
- C = Screw terminal
- E = Slow-make switching element
- F = Snap-action switching element



- A = Plug-in terminal 2.8 mm x 0.5 mm
- C = Screw terminal
- E = Slow-make switching element
- F = Snap-action switching element



- A = Plug-in terminal 2.8 mm x 0.5 mm C = Screw terminal
- E = Slow-make switching element
- F = Snap-action switching element



- A = Plug-in terminal 2.8 mm x 0.5 mm
- C = Screw terminal
- E = Slow-make switching element
- F = Snap-action switching element