

Indicator element

Distribution by Mouser



84-8001.5320







84-8001.5320 Indicator element

OPERATING-/INDICATION PART	
Illumination colour:	Green
ELECTRICAL CHARACTERISTICS	
Operating voltage:	12 V DC ±10 %
MECHANICAL CHARACTERISTICS	
Terminal:	Plug-in terminal, 2.8 x 0.8 mm
Weight:	0.005 kg
AMBIENT CONDITION	
IP Protection:	IP40
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Indicator element, Green, Single-LED, 12 V DC ± 10 %, Plug-in terminal, 2.8 x 0.8 mm
Kind of illlumination:	Single-LED
Hints:	LED and built-in resistor included, Standard version: Cable length 300 mm with insulated ferrule, plug-in terminal 2.8 mm x 0.5 mm, Other options on request: Customisation of cable and connectors, rear side fully sealed (IP 67), Protection degree (rear side): IP 40, upgrade to IP 67 with plug Part No. 84-900 possible. With applications where strong vibrations occure, the plugs may become loose, Luminosity and wave length variations caused by LED manufacturing

processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED

Wiring diagrams:

